



Gfp 400 Series Heat Assist Laminators



Increase profits with a variety of popular Pressure-Sensitive applications.

The Gfp 400 Series laminators are money makers. Easy to operate, they're a favorite with operators that prefer a simple time-saving set-up and variable roller gap adjustment. Ruggedly built for applications that require overlamination, mounting or the pre-coating of boards, the 400 Series laminators are available in 55" and 63" widths. Thanks to oversized rollers and 1 inch roller gap, you'll be making money in no time.

- **Roller diameter 4.5"**
- **Variable roller gap to 1"**
- Speed and temperature controls
- Reverse switch
- Foot pedal
- **Swing up feed table**
- 2 unwind film shafts
- 1 aluminum take-up mandrel
- Photoelectric eye
- Front unwind basket
- In feed pressure roller
- 3" core film chucks
- Dual tension control
- CE Certified
- 36" table height output
- **One-year warranty - parts & labor**



In Stock, Ready to Ship!

SPECIFICATIONS	455TH	463TH
Laminating Width	55"	63"
Roller diameter	4.5"	4.5"
Roller gap	1"	1"
Rear rewind	Optional	Optional
Max temperature	140° F	140° F
Laminating speed	0-11.5 ft/min	0-13 ft/min
Pressure adjustment	Hand wheel	Hand wheel
Heat method	Quartz tube	Quartz tube
Power supply	110v	110v
Power consumption	1100 W	1400 W
Net weight	434 lbs	509 lbs
Dimensions	72" x 23.4" x 46.5"	82" x 23.4" x 46.5"
PRICE	\$6,195	\$6,495



Simple, easy to use speed and temperature controls



Optional motorized rear rewind for roll-to-roll applications

PRICES INCLUDE:

Shipping • Setup • Training • One-Year Warranty

Training will be done by a factory authorized trainee. Aside from the basics, you will also learn the tricks of the trade to be able to laminate as a pro. Ideal for beginners and novices alike.

On display in our Brooklyn showroom. Please call to schedule a demonstration.



Master Distributors of SIGN and AWNING Materials & Equipment

110 Emerson Place, Brooklyn, NY 11205
718.399.3333 • Fax: 888.399.3375

43 Engineers Lane, Farmingdale, NY 11735
631.420.4400 • Fax: 888.399.3375